

Concrete Vibrator LXT®

DVR350

18V • 800 mm • 13 000 min⁻¹

An 800 mm shaft for easy air pocket removal

Battery-operated 18V vibrating poker. Suitable for quick and easy removal of air pockets from concrete in foundations and bases. Shaft length 800 mm and diameter 25 mm.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Vibrations per minute	13 000 min ⁻¹
Vibrator Shaft Length	0,8 m
Vibrator Shaft Diameter	25 mm
Sound Pressure Level (L _{pA})	74 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	2,9 - 3,3 kg
Product Dimensions (L x W x H):	1083 x 93 x 250 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level, Operation Without load	3,0 m/s ²
Vibration Uncertainty (K Factor), Operation Without load	1,5 m/s ²
Product net weight	2,4 kg

User benefits

- Ergonomically designed handle with rubberised soft grip
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makitauk.com



Related products

Other

User manual

Parts drawing