

VCE 33 LAC

Safety vacuum cleaner with automatic filter cleaning system, 30 l, class L

Order no. 444111

GTIN 4030293194946



- + Adapter plate for fixing L-BOXXes and Tanos systainers on the head of the vacuum cleaner
- + The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- + Continuous automatic flat filter cleaning ensures no loss of suction
- + The flat-fold filter with Teflon coating / nanocoating allows optimum use of the tank volume
- + With permanent socket and electronic automatic on/off switch
- + The flow rate control via the rotary switch minimises possible vacuums on the surface during intermediate and finish sanding
- + Suitable for wet vacuuming: with electronic liquid level control
- + Soft start stops any voltage peaks at the start and the run-on feature (15 sec. overrun) empties any remaining dust in the vacuum hose
- + Double-walled sturdy container with integrated grip recess for emptying the container easily
- + Dust-protected antistatic finish prevents electric charging of the suction hose
- + Equipped with large wheels and two swivel guide rollers made of metal
- + Separate motor air cooling duct with coarse dirt filter. Protects the turbine against the ingress of ambient air and thereby extends the service life. (Fine dust filter PES available as an accessory)
- + Simple filter change without removing the suction head
- + With hose retainer and expander for easy, quick securing of the power cable
- + With 4 clamping loops (2 on each side) for attaching straps and a giraffe holder
- + Recommendation: When working with a filter bag turn off the automatic cleaning system. When using a disposable bag leave the system on
- + Safety vacuum cleaner, approved for dust class L, suitable for all dust with OEL value $>1 \text{ mg/m}^3$



Technical data

Power consumption	1200 W
Voltage	230 V
Frequency	50/60 Hz
Vacuum cleaner flow rate	4500 m ³ /h
Max. vacuum	25000 Pa
Filter surface area	5000 cm ²
Tank volume	30 L
Liquid capacity	17 L
Suction power control	none
Hose length	4m
Number of suction motors	1 Cont.
Cable length	7.5 m
Dimensions WxLxH	565 x 385 x 565 mm
Weight	15.2 kg

Standard equipment

- 1 Antistatic suction hose with auxiliary air control (406708)
- 1 L-BOXX® holder (445169)
- 1 PES flat folded filter (445118)
- 1 Fleece filter bag (502227)
- 1 Disposal bag (445061)
- 1 Adapter (445029)
- 2 Hose clip