

Combination ladder, 3 sections

Our base model: lightweight and yet robust.

Product description

- High-quality flange connection between rungs and stiles.
- Stiles made from extruded aluminium sections for maximum stability.
- High-strength Perlon straps prevent splay.



Coating: natural
Connection between stiles and rungs/stiles: flanged

Load: max. 150 kg Material: aluminium Tread depth: 24 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 265 mm



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2- part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Transport dimensions	Weight	Wide crosspiece	Working height as 3-part single ladder
48980	4 m	2.53 m	7	3×7	2.04 m	approx. 2.038 mm × approx. 460 mm × approx. 135 mm	9.9 kg	0.74 m	max. approx. 4.8 m
48981	5.12 m	3.37 m	8	3 × 8	2.32 m	approx. 2.318 mm × approx. 460 mm × approx. 180 mm	13.3 kg	0.88 m	max. approx. 5.9 m
48982	5.96 m	3.93 m	9	3 × 9	2.6 m	approx. 2.598 mm × approx. 460 mm × approx. 190 mm	14.9 kg	0.99 m	max. approx. 6.7 m
48983	6.52 m	4.49 m	10	3 × 10	2.88 m	approx. 2.878 mm × approx. 460 mm × approx. 200 mm	16.9 kg	0.99 m	max. approx. 7.2 m
48984	6.8 m	4.77 m	11	3 × 11	3.16 m	approx. 3.158 mm × approx. 460 mm ×	20.1 kg	1.2 m	max. approx. 7.5 m

ZARGES (U.K.) Ltd. 8 Holdom Avenue. Saxon Park Ind. Est. Bletchley MK1 1QU Tel: 01908 641118 Fax: 01908 641118 www.zarges.com sales@zarges.co.uk

Effective 12/4/2020



approx. 220 mm